UTILITY PATENT APPLICATION **TRANSMITTAL**

Attorney Docket No. 042390.P5769 Total Pages 22 First Named Inventor or Application Identifier Gang Bai

(Only for new nonprovisional applications under 37 CFR 1 53(b))

Express Mail Label No. EM014063345US

APPLICATION ELE See MPEP chapter 600 concerning utility p	ADI	DRESS TO:	Box Pa	ant Commissio Itent Application Ington, DC 202		
Fee Transmittal Form (Submit an onginal, and a duplicate Specification (preferred arrangement set forth be Descriptive title of the Interpretation Cross References to Relational Regarding Fed	[Total Pages 18 Identify vention ated Applications at sponsored R & D Appendix	7	7. Nucleotide and/or (if applicable, all I a. Compu	Amino necess ter Re Copy	o Acid Seque sary) adable Copy (identical to d	
1 *	Background of the Invention Brief Summary of the Invention			YING	APPLICA	TION PARTS
- Brief Description of the D - Detailed Description - Claim(s) - Abstract of the Disclosur 3. Drawing(s) (35 CFR 113) 4. Oath or Declaration a. Newly execute b. Copy from a procommatorities and in the control of the Disclosur [Note B i. DELETIO Signed stinventor(s)	re [Total Sheets 1 [Total Pages] In application (37 CF In Box 17 cmpleto) NOF INVENTOR(S) Itatement attached des) named in the prior FR 1.63(d)(2) and 1.3 Ite (usable if Box 4b is checked prior application, fration is supplied undurt of the disclosure o	eleting 14 application, 33(b). 15 cked) 16 om which a 16 er Box 4b, 16	37 CFR 3.73 (when there is an D. English Trans D. Information I Statement (II Preliminary A B. Return Rece (Should be spec	b) Sta assigned lation Disclos DS)/P1 .mend pt Posifically ite	tement (ii) Document (ii) sure TO - 1449 ment stcard (MPE) emized) Statement Status still riority Document	Copies of IDS Citations P 503) filed in prior application, proper and desired
17. If a CONTINUING APPLIC					nation No:	
Continuation Div		inuation-in-par	t (CIP) ot prior	appiic	ation No:	
Customer Number of Bar Code Label (Insert Customer No or Attach bare code label here) Customer Number of Bar Code Label						
BLAKE	BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP					
• NAME						
ADDRESS 12400 W	12400 Wilshire Boulevard, Seventh Floor					
CITY Los Ang	Los Angeles STA		California ZIF		IP CODE	90025
		TELEPHONE	(310) 207-380)	FAX	(310) 820-5988

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL

Note: Effective October 1, 1997. Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT

790.00

Complete if Known					
Application Number					
Filing Date	06/30/98				
First Named Inventor	Gang Bai				
Group Art Unit					
Examiner Name					
Attorney Docket Number	042390.P5769				

METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)					
The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:	3. ADDITIONAL FEE					
Deposit	Large Entity Small Entity					
Account 02-2666	Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$)					
Number	105 130 205 65 Surcharge - late filing fee or oath					
Deposit Account Blakely, Sokoloff, Taylor & Zafman LLP	127 50 227 25 Surcharge - late provisional filing fee or					
Name	cover sheet.					
Charge Any Additional Charge the Issue Fee Set in 37 Fee Required Under 37 CFR 1 18 at the Mailing of the	139 130 139 130 Non-English specification					
CFR 1 16 and 1.17 Notice of Allowance, 37 CFR	147 2,520 147 2,520 For filing a request for reexamination					
1 311(b)	112 920 112 920 Requesting publication of SIR prior to					
2. X Payment Enclosed:	Examiner action					
Check Money Other	113 1,840 113 1,840 Requesting publication of SIR after Examiner action					
FEE CALCULATION (fees effective 10/01/96)	115 110 215 55 Extension for response within first month					
	116 400 216 200 Extension for response within second month					
1. FILING FEE	117 950 217 475 Extension for response within third month					
Large Entity Small Entity Fee Fee Fee Fee Description Fee Paid	118 1,510 218 755 Extension for response within fourth month					
Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$)	119 310 219 155 Notice of Appeal 120 310 220 155 Filing a brief in support of an appeal					
101 790 201 395 Utility filing fee \$790	• • • • • • • • • • • • • • • • • • • •					
106 330 206 165 Design filing fee	138 1,510 138 1,510 Petition to institute a public use proceeding					
107 540 207 270 Plant filing fee	140 110 240 55 Petrion to revive unavoidably abandoned					
108 790 208 395 Reissue filing fee	application					
114 150 214 75 Provisional filing fee	141 1,320 241 660 Petrion to revive unintentionally					
SUBTOTAL (1) (\$) 790.00	abandoned application 142 1,320 242 660 Utility issue fee (or reissue)					
Fee from 5- paid	1 142 1,320 242 660 Utility issue fee (or reissue) 143 450 243 225 Design issue fee					
2. CLAIMS Extra Fee from Fee Paid	144 670 244 335 Plant issue fee					
Total Claims 14 -20 = 0 X \$22.00 = 0.00						
Independent 0 0 0 000 00 000 000 000	41					
Claims 2 -3 = 0 X \$82.04 = 0.00 Multiple Dependent Claims =	126 240 126 240 Submission of Information Disclosure Stmt					
Large Entity Small Entity Fee Fee Fee Fee Description	581 40 581 40 Recording each patent assignment per property (times number of properties)					
Code (\$) Code (\$)	146 790 246 395 Filing a submission after final rejection					
103 22 203 11 Claims in excess of 20	(37 CFR 1.129(a))					
102 82 202 41 Independent claims in excess of 3	149 790 249 395 For each additional invention to be examined (37 CFR 1.129(b))					
104 270 204 135 Multiple Dependent claim	Other fee (specify)					
109 82 209 41 Reissue independent claims over original patent	Other fee (specify)					
110 22 210 11 Reissue claims in excess of 20	Other roe (apectry)					
and over original patent						
SUBTOTAL (2) (\$) 0.00	*Reduced by Basic Filing Fee Pard SUBTOTAL (2) (\$)					
	1 Educated by Educat Integrition 1 and					

UNITED STATES PATENT APPLICATION

FOR

A MULTI-LAYER GATE DIELECTRIC

Inventor:

Gang Bai

Prepared by:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP 12400 Wilshire Boulevard, Seventh Floor Los Angeles, California 90025 (310) 207-3800

5

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to integrated circuit devices and more particularly to enhancing dielectric material in those device.

Description of Related Art

One way to improve integrated circuit performance is through scaling the individual devices that comprise the integrated circuit. Thus, each subsequent generation of integrated circuit generally involves reducing the size of the individual devices on, for example, a semiconductor chip. The Morse rule is a common benchmark in the integrated circuit technology and provides that devices will be scaled down or reduced in size by one-third for each new generation.

The scale of a transistor device requires consideration of the desired performance of the device. For example, one goal may be to increase the current flow in the semiconductor material of the transistor. The current flow is proportional to the voltage applied to the gate electrode and the capacitance seen at the gate:

 $Q \propto C(V-V_{th})$

20

25

5

where O is one measure of the current flow, C is capacitance, V is the voltage applied to the gate electrode, and V_{th} is the threshold voltage of the device.

To increase the voltage applied to a device requires an increase in power, P (P \propto V²). However, at the same time as increasing the charge in the transistor, subsequent generations also seek to reduce the power required to run the device, since, importantly, a reduction of power reduces the heat generated by Thus, to increase the current flow through the the device. device without increasing the power requires an increase in the capacitance in the gate.

One way to increase the capacitance is by adjusting the thickness of the gate dielectric. In general, the capacitance is related to the gate dielectric by the following formula:

$C = k_{ox}/t_{electrical}$

where k_{ox} is the dielectric constant of silicon dioxide (SiO₂) and telectrical is the electrical thickness of the gate dielectric. The electrical thickness of the gate dielectric is greater than the actual thickness of the dielectric in most semiconductor devices. In general, as carriers flow through the channel of a semiconductor-based transistor device there is a quantum effect experienced in the channel which causes an area directly below the gate to become insulative. The insulative region acts like an extension of the gate dielectric by essentially extending the dielectric into a portion of the

25

5

channel. The second cause of increase gate dielectric thickness attributable to $t_{\rm electrical}$ is experienced by a similar phenomenon happening in the gate electrode itself. At inversion, a gate electrode of polysilicon, for example, will generally experience a depletion of carriers in the area of the polysilicon near the gate dielectric. Accordingly, the gate dielectric appears to extend into the polysilicon gate electrode.

The result of the quantum effect in the channel and a depletion in the polysilicon gate electrode is an electrical thickness (t_{electrical}) of the gate dielectric greater than the actual thickness of the gate dielectric. The magnitude of the channel quantum effect and polysilicon depletion may be estimated or determined for a given technology. Accordingly, the electrical thickness (t_{electrical}) for a SiO₂ may be calculated and scaled for a given technology.

In considering the capacitance effects of the gate dielectric, a consideration of the thickness of gate dielectric is important for other reasons. First, the gate dielectric cannot be too thin as a thin gate dielectric will allow a leakage current from the channel through the gate electrode. At the same time, the gate dielectric cannot be too thick because such a gate structure may produce an undesirable fringe electric field. The desired electric field at the gate is typically perpendicular to the surface of the semiconductor substrate. Beyond a certain gate dielectric thickness, generally thought to

be beyond one-third the lateral width of the gate electrode for a SiO_2 gate dielectric, the electrical field deviates from a perpendicular course and sprays about the gate electrode leading to an undesirable fringe electric field.

5

What is needed is a way to increase the capacitance of a gate dielectric without decreasing the performance of the device. It is preferable if the increased capacitance is consistent with scaling techniques and may be used in multiple generation technologies.

SUMMARY OF THE INVENTION

A transistor gate dielectric is disclosed. The transistor gate dielectric includes a first dielectric material having a first dielectric constant and a second dielectric material having a second dielectric constant different from the first dielectric constant.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration of a side view of a transistor dielectric having a gate dielectric of a first dielectric material and a second dielectric material.

5

DETAILED DESCRIPTION OF THE INVENTION

The invention relates to a transistor gate dielectric made up of at least two different dielectric materials. For example, one embodiment contemplates a gate dielectric made up of two different dielectric materials each with its own dielectric The dielectric material nearest the substrate, e.g., constant. a semiconductor substrate will have a modest dielectric constant that produces a defect-free interface with the substrate and is stable against oxide formation. The second dielectric material will have a relatively high dielectric constant and be stable in contact with the desired gate material. By varying the thickness of the material, a gate dielectric can be formed that is scalable for different technology generations, has a low leakage current, and maintains an electric field of the gate perpendicular to the surface of the semiconductor. A transistor gate utilizing the multi-layer gate dielectric is also disclosed.

Figure 1 illustrates an embodiment of the multi-layer gate dielectric of the invention. Figure 1 shows transistor 100 consisting of gate electrode 110 overlying gate dielectric 140. Gate electrode 110 and gate dielectric 140 overlie semiconductor substrate 105 such as, for example, a silicon semiconductor substrate. Formed in substrate 105 adjacent transistor gate electrode 110 are diffusion or junction regions 160. The

transistor is isolated from other devices, in this example, by shallow trench isolation structures 150.

Gate dielectric 140 is made up of, in this example, a bilayer gate dielectric stack. The gate dielectric material is deposited by conventional techniques such as chemical vapor deposition or other deposition techniques according to the specifics of the material. The individual dielectric materials that make up the gate dielectric stack are patterned using conventional techniques such as masking and etching.

5

In one embodiment, the bottom dielectric layer 130 is selected to have a modest dielectric constant, k1, that forms a generally defect-free interface with substrate 105. A generally defect-free interface is one that has a sufficiently high (e.g., >8 MV/cm) dielectric breakdown strength implying that the dielectric layer is pin-hole free and contains a negligible number of defects that would lead to breakdown of the dielectric layer at lower electric fields. Bottom dielectric layer 130 should also be stable on silicon and stable against oxide formation. In one embodiment, bottom dielectric layer 130 materials are chosen that have a heat of formation greater than the heat of formation of SiO2. The chemistry in terms of stability of bottom layer 130 is important to achieve the low defect interface. Examples of suitable bottom dielectric layer 130 include, but are not limited to, hafnium oxide (HfO2), zirconium oxide (ZrO2), barium oxide (BaO), lanthanum oxide (La₂O3), and yttrium oxide (Y_2O_3) .

25

20

5

10

In this embodiment, top dielectric layer 120 is selected to have a relatively high dielectric constant, k_2 , and is a material that is stable in contact with gate electrode 110. Examples of suitable top dielectric layers are BaSrTiO3 (BST) and PbZrTiO3 (PZT). One function of top dielectric layer 120 is to block any leakage current through bottom dielectric layer 130, without adding to the equivalent thickness of gate dielectric 140 (i.e., equivalent thickness of an SiO_2 gate dielectric) and contributing to the production of a fringe electric field.

One guideline to select the appropriate dielectric layer thickness t_1 for bottom dielectric layer 130, and t_2 for top dielectric layer 120, is the following. For a given technology generation (i.e., a given gate length of gate electrode 110 and equivalent oxide thickness of a SiO₂ gate dielectric, $t_{\rm ox}$), a total thickness, t, of gate dielectric 140 should be less than one-third of the gate length of gate electrode 110. The effective dielectric constant, k, may then be determined by the following relationship:

$$k = k_{ox} (t/t_{ox})$$
 (1)

wherein k_{ox} is the dielectric constant of SiO_2 which is typically represented as 4.0.

Combining the above relationship with a relationship for calculating the effective dielectric constant of gate dielectric 140 of the following:

$$k = t/(t_1/k_1 + t_2/k_2),$$
 (2)

the total thickness of dielectric layer 140 may be calculated:

$$t = t_1 + t_2 \tag{3}$$

Combining equations (1), (2), and (3) yields the following:

$$t_1/k_1 + t_2/k_2 = t_{ox}/k_{ox}$$
. (4)

Equation (4) is then solved for a thickness of bottom dielectric layer 130 having a known dielectric constant, k_1 , and top dielectric layer 120 also having a known dielectric constant, k_2 . Table I shows the individual thicknesses of first dielectric layer 130 (t_1) and second dielectric layer 120 (t_2) for various technologies scaled by the Morse rule starting with a gate electrode length of 150 nanometers, for a k_1 of 30 and a k_2 of 300.

Table I demonstrates that a multi-layer dielectric gate stack, in this case, a bi-layer dielectric gate stack, is scalable for a given technology. For example, for each technology, given a first dielectric layer 130 having a dielectric constant k_1 of 30 and a second dielectric layer 120 having a dielectric constant k_2 of 300, a total gate dielectric layer thickness less than one-third of the individual gate lengths is maintained. Further, the choice of second gate dielectric layer 120 of material to block the leakage current maintains the performance of the device. Finally, by manipulating the gate dielectric materials, the capacitance of

the device may be appropriately increased for the given technology.

For a gate electrode 110 that is polysilicon, a third dielectric layer may be utilized to act as a barrier layer to prevent interaction between top dielectric layer 120 materials having high dielectric constants and the polysilicon gate material. Suitable third dielectric materials include, but are not limited to, HfO₂, ZrO₂, BaO, La₂O₃, and Y₂O₃ (notably the same materials suitable as bottom dielectric layer 130).

The above example is described with respect to gate electrode 110 being a polysilicon. It is to be appreciated that the same principles may be applied to gate electrodes of different materials, such as, for example, metal gates. In the case of a metal gate electrode, the electrical thickness (telectrical) may be reduced since, in general, metal gate electrodes do not experience the depletion seen by polysilicon. Table I also shows the scaling of the bi-layer dielectric materials discussed above using metal gate technology.

Technology Generation	1	2	3	4	5	6
Lgate (nm)	150	100	70	50	35	25
t_electrical (Å)	30	21	15	10	7	5
t_ox (Å):metal gate	26	17	11	6	3	1
t (Å):total stack thick	300	210	147	103	72	50
t_1 (Å), $k_1=30$	183	118	75	39	17	3
t_2 (Å), $k_2 = 300$	117	92	72	64	55	48

Table I

In the preceding detailed description, the invention is described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed:

- A transistor gate dielectric comprising: 1 1.
- a first dielectric material having a first dielectric 2
- 3 constant; and
- a second dielectric material having a second dielectric 4
- constant different from the first dielectric constant. 5
- Hart the the transfer than the same The transistor gate dielectric of claim 1, wherein the 2.
 - second dielectric constant is greater than the first dielectric
 - constant.
- 1 2 3 The transistor gate dielectric of claim 1, wherein the
 - first material has a first thickness and the second material has
 - a second thickness, the combination of the first thickness and
 - the second thickness defining a total thickness less than one-4
 - third of the length of a transistor gate adapted to overly the 5
 - 6 gate dielectric.
 - The gate dielectric of claim 3, wherein the first material 1
 - thickness and the second material thickness are determined by 2
 - 3 the relationship

4

$$t_1/k_1 + t_2/k_2 = t_{ox}/k_{ox}$$

- 5 wherein t_1 is the first material thickness,
- 6 t₂ is the second material thickness,
- 7 tox is the minimum thickness for a gate dielectric of
- 8 silicon dioxide for a chosen gate length,
- 9 k₁ is the dielectric constant for the first dielectric
- 10 material,
- 11 k₂ is the dielectric constant for the second
- 12 dielectric material, and
- 13 k_{ox} is the dielectric constant of silicon dioxide.
- 1 5. The gate dielectric of claim 1, wherein the first gate
- 2 dielectric material is selected from one of silicon nitride,
- 3 HfO_2 , BaO, La₂O₃, Y₂O₃, and ZrO₂.
- 1 6. The gate dielectric of claim 1, wherein the second
- 2 dielectric material is selected from one of BST and PZT.
- 1 7. The gate dielectric of claim 1, further comprising a third
- 2 dielectric material having a third dielectric constant.
- 1 8. A transistor having a gate electrode overlying a gate
- 2 dielectric comprising:
- 3 a first dielectric material having a first dielectric
- 4 constant; and
- 5 a second dielectric material having a second dielectric
- 6 constant different from the first dielectric constant.

- 1 9. The transistor of claim 8, wherein the second dielectric of
- 2 the gate dielectric has a dielectric constant greater than the
- 3 first dielectric constant.
- 1 10. The transistor of claim 8, wherein the first material of
- the gate dielectric has a first thickness and the second
- 3 material of the gate dielectric has a second thickness, the
- 4 combination of the first thickness and the second thickness
- 5 defining a total thickness less than one-third of a length of
- 6 the transistor gate electrode.
- 1 11. The transistor of claim 8, wherein the first material
- 2 thickness and the second material thickness are determined by
- 3 the relationship
- $4 t_1/k_1 + t_2/k_2 = t_{ox}/k_{ox}$
- 5 wherein t₁ is the first material thickness,
- 6 t₂ is the second material thickness,
- 7 tox is the minimum thickness for a gate dielectric of
- 8 silicon dioxide for a chosen gate electrode length,
- 9 k₁ is the dielectric constant for the first dielectric
- 10 material,
- 11 k₂ is the dielectric constant for the second
- 12 dielectric material, and
- k_{ox} is the dielectric constant of silicon dioxide.

- 1 12. The transistor of claim 8, wherein the first gate
- dielectric material is selected from one of silicon nitride,
- 3 HfO_2 , BaO, La₂O₃, Y₂O₃, and ZrO₂.
- 1 13. The gate dielectric of claim 8, wherein the second
- dielectric material is selected from one of BST and PZT.
- 1 14. The gate dielectric of claim 8, further comprising a third
- dielectric material having a third dielectric constant.

ABSTRACT OF THE DISCLOSURE

A transistor gate dielectric including a first dielectric material having a first dielectric constant and a second dielectric material having a second dielectric constant different from the first dielectric constant.





Fig. 1

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

		cause:		suitable for scanning and are not in compliance with 37 CFR 1.52
		Pages Papers are re Papers contained	not flexible, not typewrit ain imprope and top, bo	do not meet these requirements. strong, smooth, non-shiny, durable, and white. ten or mechanically printed in permanent ink on one side. er margins. Each sheet must have a left margin of at least ottom and right margins of at least 2.0 cm (3/4"). tering.
2.		The drawing All drawings or 8-1/2" x 1 Each sheet m	s or copy o s sheets are 1". aust include	f drawings are not suitable for electronic reproduction. not the same size. Pages must be either A4 (21 cm x 29.7 cm) a top and left margin of at least 2.5 cm (1"), a right margin of and a bottom margin of at least 1.0 cm (3/8").
3.	Page repr	e(s)oduction.		_ are not of sufficient clarity, contrast and quality for electronic
4.	Page	(s)	- 	_ are missing.
5.	ОТН	ER:	No	Jecla ration